

# MATRIX SERIES

## COLUMN ARRAY SERIES

### OVERVIEW

The MATRIX passive column arrays are composed of closely-spaced state of the art, 3" neodymium transducers housed in a stylish and yet sturdy aluminum/wood chassis for excellent Architectural Integration.

These speaker arrays have been developed in order to offer the highest intelligibility at high SPL and wider frequency response while providing constant beam-width over a user selectable vertical coverage. This accurate beam control extends up to 10kHz, well beyond the benchmark of 4kHz of traditional single-driver loudspeakers.

To better control the lower frequencies, the Tuned Dipolar Technology was developed by NEXT-proaudio engineers to provide much more consistent low frequency pattern control than other similar size systems.

A user selectable Music / Vocal mode switch is incorporated to allow quick and easy system optimization. Music mode provides a flat, balanced frequency response, while Vocal mode adds a mid-range presence for enhanced speech intelligibility.

NEXT MATRIX column arrays are able to focus the acoustical energy where it is needed, the listening area, leading to significant improvements to speech intelligibility and musical clarity even in critical acoustic environments.

For even greater versatility, the vertical dispersion pattern can be switched for Wide or Narrow coverage.

Small conventional column loudspeakers arrays provide no significant vertical directivity control at lower frequencies due to their physical size.

To better control the lower frequencies, the Tuned Dipolar Technology was developed to provide more consistent low frequency pattern control than other similar size systems. This can be useful in reducing the stimulation of resonant room modes at low frequencies.

The heart of the NEXT MATRIX column arrays is the internal processing board. This proprietary special circuitry takes care of the array optimization and allows the user to easily adjust the system behavior to meet the application requirements.

For an architectural integrated installation, a 16mm cavity in the back of the speaker provides ample space for hidden speaker wiring, even when the speaker is mounted flat against a wall.

Removable Input screw connector offers reliable, easier and more efficient wiring.

A variety of accessories is available to provide linking, hanging, and wall or pole mounting. For high-impedance (100V) operation, an optional multi tap transformer is available.

PAGE

24

**M3**

Passive Column  
Array



PAGE

24

**M8**

Passive Column  
Array



# MATRIX SERIES

## COLUMN ARRAY SERIES

### M3

#### Passive Column Array

- | Variable Beam Shaping
- | Tuned Dipolar Technology
- | Simple and Discreet Install
- | Vocal and Music Selector
- | 100V - 40W Transformer (optional)



### M3

SPEAKER TYPE	Tuned Dipolar, Variable Beam Straight Line Array
DRIVERS	3 x 3" (70mm)/0.75" (20mm) VC, custom neodymium speaker
FREQ. RESPONSE (-10dB) (with dedicated preset)	140Hz - 20kHz
EQ. OPTIMIZATION MODE	Vocal or Music (User Selectable)
HORIZONTAL COVERAGE	90° (+/-20° 1.5-5kHz)
VERTICAL COVERAGE (Wide/Narrow)	40° (+/-10° 2-16kHz) / 15° (+/-10° 3-16kHz)
SENSITIVITY (1W@1m) (Vocal/Music)	96dB/93dB
Calc. Max. SPL Vocal (Continuous/Peak)	118.6dB/121.6dB
Calc. Max. SPL Music (Continuous/Peak)	115.6dB/118.6dB
PROGRAM POWER	180W
NOMINAL IMPEDANCE	8Ω
RECOMMENDED AMPLIFIER	MA900
RECOMMENDED SUBWOOFER	K12s, K12sA, HFA115s
ENCLOSURE	Aluminum / Wood / Steel / 3D Fabric
STANDARD ENCLOSURE COLOR	Black or White
CONNECTORS	4 Pins Screw Connector (IN/OUT)
DIMENSIONS (WxHxD)	108 x 296 x 152mm (4.25 x 11.65 x 5.98in)
WEIGHT	2.6kg (5.73lb)

### M8

#### Passive Column Array

- | Variable Beam Shaping
- | Tuned Dipolar Technology
- | High intelligibility at high SPL
- | Vocal and Music Selector
- | 100V - 80W Transformer (optional)



### M8

SPEAKER TYPE	Tuned Dipolar, Variable Beam Straight Line Array
DRIVERS	8 x 3" (70mm)/0.75" (20mm) VC, custom neodymium speaker
FREQ. RESPONSE (-10dB)	135Hz - 20kHz
EQ. OPTIMIZATION MODE	Vocal or Music (User Selectable)
HORIZONTAL COVERAGE	90° (+/-20° 1.5-5kHz)
VERTICAL COVERAGE (Wide/Narrow)	25°(+/-10° 1.2-16kHz) / (+10°/-5° 1.5-16kHz)
SENSITIVITY (1W@1m)	100dB/97dB
Calc. Max. SPL Vocal (Continuous/Peak)	126.1dB/129.1dB
Calc. Max. SPL Music (Continuous/Peak)	123.1dB/126.1dB
PROGRAM POWER	480W
NOMINAL IMPEDANCE	8Ω
RECOMMENDED AMPLIFIER	MA1700
RECOMMENDED SUBWOOFER	HFA115s, HFA115sHP, HFA118sHP
ENCLOSURE	Aluminum / Wood / Steel / 3D Fabric
STANDARD ENCLOSURE COLOR	Black or White
CONNECTORS	4 Pins Screw Connector (IN/OUT)
DIMENSIONS (WxHxD)	108 x 677 x 152mm (4.25 x 26.65 x 5.98in)
WEIGHT	6.2kg (13.7lb)

